

## PRODUCT DESCRIPTION

Super Cleaner is a highly concentrated cleaner. Removes wax, oil and contamination effectively. Suitable for hand and high pressure machine washing. Degreases and cleans with no damage to gelcoat or paintwork. Always use before waxing.

- \* Very effective degreasing when used at higher concentrations.
- \* Easy to use
- \* Does not damage plexiglass.
- \* Use before painting or waxing.
- \* Also suitable for general cleaning on the boat, bilge/engine or car.
- \* Biodegradable.

## PRODUCT INFORMATION

<b>Colour</b>	YMA620-Yellow-brown
<b>Specific Gravity</b>	0.98
<b>Mix Ratio</b>	Number of caps to one litre of water:- Normal cleaning 5 caps. Heavy cleaning and degreasing 10 caps. Prior to waxing, painting or bilge/engine cleaning 20 caps.
<b>Unit Size</b>	500 ml

## DRYING/OVERCOATING INFORMATION

### Drying

### Overcoating Substrate Temperature

Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max
---------------	-----	-----	-----	-----	-----	-----	-----	-----

## APPLICATION AND USE

<b>Preparation</b>	Rinse with fresh water and allow to dry.
<b>Method</b>	Choose appropriate mixing ratio. Add the required number of capfuls of Super Cleaner to fresh water. Apply Super Cleaner to a damp cloth or sponge, then wipe the whole surface to be cleaned using moderate pressure. Rinse with fresh water.
<b>Hints</b>	<b>Mixing</b> Shake well before use.
<b>Some Important Points</b>	Product temperature should be minimum 5°C and maximum 30°C. Ambient temperature should be minimum 5°C and maximum 30°C. Substrate temperature should be minimum 5°C and maximum 30°C.
<b>Compatibility/Substrates</b>	Suitable for use on GRP and painted surfaces. Not sensitive to frost.
<b>Recommended DFT</b>	
<b>Application Methods</b>	Brush /Cloth/Sponge.

## TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Super Cleaner to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/40°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION:</b>
----------------	--

Super Cleaner should be kept in securely closed containers during transport and storage.

## Safety

**GENERAL:** Read the label safety section for Health and Safety Information, also available from our Technical Help Line.

**DISPOSAL:** Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal.

Remainders of Super Cleaner cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

## IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal or injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

**X** and International are registered trademarks of Akzo Nobel.

## Regional Addresses

Head Office  
International Paint Ltd  
P O Box 20980  
Oriol House  
16 Connaught Place  
London W2 2ZB  
United Kingdom  
tel: +44 (0) 171 479 6000  
fax: +44 (0) 171 479 6500

European Region  
International Paint Ltd  
Stoneygate Lane  
Felling, Gateshead  
Tyne & Wear NE10 0JY  
United Kingdom  
tel: +44 (0) 191 469 6111  
fax: +44 (0) 191 438 3977

Asia Region  
International Paint Singapore  
(Pte) Ltd  
449 Tagore Industrial Avenue  
01-03 Hong Joo Industrial  
Building  
Singapore 787820  
tel: +65 6453 1981  
fax: +65 6453 1778

Australasia Region  
International Paint  
115 Hyde Road  
Yeronga, Brisbane  
Queensland 4104  
Australia  
tel: +61 (0) 7 3892 8866  
fax: +61 (0) 7 3892 4287

North America Region  
International Paint Inc  
2270 Morris Avenue  
Union  
New Jersey 07083  
USA  
tel: +1 (0) 908 686 1300  
fax: +1 (0) 908 686 8545

South America Region  
International Paint  
Rod Rap tavares, KM 18.5  
Predio Administrativo 11  
Butanta CEP 05577-300  
Sao Paulo, Brazil  
tel: +55 (0) 11 3789 2000  
fax: +55 (0) 11 3789 2200



Ref: 05000147  
Issue Date: 4-Sep-2004  
Supersedes: 22-Sep-2003