

Textile Waterproofer

Boatcare

Water-based Water Barrier for Textiles



PRODUCT DESCRIPTION

Water-based Textile Waterproofer provides an effective water barrier for textiles used in the boating industry.

- * Water-based environmentally friendly formulation.
- * Suitable for covers, canopies, sprayhoods and other textiles.
- * No discolouration and no loss of flexibility.

PRODUCT INFORMATION

Colour	Transparent
Specific Gravity	0.77
Volume Solids	10%
VOC (As Supplied)	0 g/l
Unit Size	500 ml

DRYING/OVERCOATING INFORMATION

Drying

Overcoating

Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

APPLICATION AND USE

Method	Spray apply textile waterproofer evenly over the item to be treated until surface is saturated. Allow to dry. Repeat the treatment after a couple of months. Can be diluted with water to allow application by submerging textile in diluted solution.
Hints	Mixing Shake well before use. Other Drying time depends on wind, temperature and humidity.
Some Important Points	Contains fluoro-carbons. Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
Compatibility/Substrates	For use on most types of textiles. Always check a hidden area for colour fastness. Do not use on glass.

TRANSPORTATION, STORAGE AND SAFETY INFORMATION

Storage	GENERAL INFORMATION: Exposure to air and extremes of temperature should be avoided. For the full shelf life of Textile Waterproofer to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. TRANSPORTATION: Textile Waterproofer should be kept in securely closed containers during transport and storage.
Safety	GENERAL: Read the label safety section for Health and Safety Information, also available from our Technical Help Line. DISPOSAL: Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Textile Waterproofer cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

IMPORTANT NOTES

The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.

Please refer to your local representative or visit www.yachtpaint.com for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2015.