



PAINT STRIPPER

A.S

PAINT STRIPPER FOR ANTIFOULING, AND ONE-POT VARNISH

DESCRIPTION

NAUTIX A.S. paint stripper is recommended to remove enamels, varnishes, and non-slip Nautix grip.

It's particularly adapted to strip antifouling, except those containing tin.

It does not attack gelcoat and does not contain neither acid nor base.

Nautix A.S. is a degradable product to respect the E.C. directive concerning boat hull cleaning : no soil pollution, no use of fresh water.

The clean of the hull is easy if it's carried out every 2-3 years.

COMPOSITION

Methylpyrrolidone

Dimethyladipate

PREPARATION - APPLICATION

Apply the gel over a 1-2 sqm surface with a brush or a roller.

Let the product impregnate for 30 min (at 15°C) until the paint becomes soft.

Then strip paint and paper together using a metallic spatula.

Collect waste in an appropriate container.

If it is required to remove many years of paint, this operation can be repeated as many times as necessary.

Finish the cleaning with paint thinner (NAUTIX DA for antifouling) or NAUTIX Solvent Degreaser and sand the surface.

DRYING TIME

Temperature	10°C	15°C	20°C	25°C
Hand dry	50 min	30 min	15 min	10 min

TECHNICAL DATA

Pack sizes : 0,75L et 2,5L

Appearance : incolor gel

Coverage : 3 à 4 m²/l to removed 3 last coats of paints.

Flash point : T₅₀65°C

SAFETY DATA

R 36/38 Irritating to eyes and skin.

S 2 Keep out of the reach of children.

S 46 If swallowed, seek medical advice immediately and show this container or label.

Emergency phone number : +33 (0)1 45 42 59 59

NAUTIX S.A.

Z.I. des 5 Chemins

56520 GUIDEL

FRANCE

Fax : + 33 (0)2 97 65 03 54

Tel : + 33 (0)2 97 65 32 69

E.mail : info@nautix.com

www.nautix.com