

Sika[®] Remover-208

Technical product data:

Chemical base	petroleum distillate (free of aromatic solvents)
Colour	transparent
Density (DIN 51757)	0,76 kg/l approx.
Viscosity	1 mPas
Flash point (DIN 51755)	> 24°C
Drying time (23°C / 50% R.H.)	30 minutes minimum to 24 hours maximum
Storage	store in sealed container in a cool dry place
Shelf life	24 months
Transport	classified as a hazardous substance. Safety Data Sheet is available from Sika on request.

Description:

Sika[®] Remover-208 is used to remove traces of Sikaflex[®] products as well as pre-cleaning painted substrates.

Areas of application:

- Sika[®] Remover-208 can be used to remove excess uncured Sikaflex[®] adhesive or sealant from application tools or from soiled surfaces.
- Sika[®] Remover-208 can also be used for the pre-cleaning of strongly contaminated non-porous substrates.
- Sika[®] Remover-208 can be used to clean painted surfaces prior to bonding. Use Sika[®] Remover-208 according to Sika Primer Chart.

Method of application:

- Remove the bulk of the Sikaflex[®] residue with a knife or spatula. Moisten a cloth with Sika[®] Remover-208 and wipe off the remaining traces of adhesive or sealant.
- Wipe painted surfaces with a moistened cloth with Sika[®] Remover-208. Let dry well prior to the application of adhesives or sealants.

Note: Sika[®] Remover-208 must not be used to clean soiled skin.

For information and advice on the safe handling, storage and disposal of chemical products, users should refer to the current Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

Further information:

Copies of the following publications are available on request:

- Sika Primer Chart
- Safety Data Sheet

Note:

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.