



MATERIAL SAFETY DATA SHEET

Sika Remover 208

HMIS

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	H

1. Product And Company Identification

Supplier Sika Corporation 201 Polito Ave Lyndhurst, NJ 07071 Company Contact: EHS Department Telephone Number: 201-933-8800 FAX Number: 201-933-9379 Web Site: www.sikausa.com	Manufacturer Sika Schweiz AG Tuffenwies 16 Zurich, Schweiz CH-8048 Switzerland Telephone Number: +41 44 436 40 40 FAX Number: +41 44 436 47 36
Supplier Emergency Contacts & Phone Number CHEMTREC: 800-424-9300 INTERNATIONAL: 703-527-3887	Manufacturer Emergency Contacts & Phone Number Out of office hours only: +41 (0) 79 309 06 29

Issue Date: 11/15/2007
Product Name: Sika Remover 208
CAS Number: Not Established
MSDS Number: 4217
Product Code: I2081000

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	64742-48-9	

3. Hazards Identification

Eye Hazards
 May cause eye irritation.

Skin Hazards
 May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

Ingestion Hazards
 Harmful if swallowed. May cause lung damage if swallowed.

Inhalation Hazards
 May cause nose, throat, and lung irritation. Breathing in large amounts may cause central nervous system effects (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

MATERIAL SAFETY DATA SHEET

Sika Remover 208

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

Ingestion

If swallowed, do not induce vomiting unless directed to do so by medical personnel.

Inhalation

Remove to fresh air. If not breathing, give artificial respiration, seek medical attention.

5. Fire Fighting Measures

Flash Point: >75.2 °F >24 °C

Fire And Explosion Hazards

Flammable liquid and vapor. Protect against electrostatic charge. Possible formation of explosive mixtures air/vapor. Above flash point, vapor-air mixtures are explosive within flammable limits notes above. Vapors may flow along surfaces to distant ignition sources and flash back. Sealed containers may rupture when heated.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

Eliminate all ignition sources. Use appropriate Personal Protective Equipment (PPE). Absorb and/or contain spill with inert materials (e.g. sand, vermiculite) and then place in appropriate container. For large spills, use water spray to disperse vapors. Prevent runoff from entering waterways or sewers.

7. Handling And Storage

Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

Handling Precautions

Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors, and static electricity).

Storage Precautions

Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Store in a cool, dry, well-ventilated area.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use of a system of local and/or general exhaust is recommended to keep employee below applicable exposure limits. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

MATERIAL SAFETY DATA SHEET

Sika Remover 208

8. Exposure Controls/Personal Protection - Continued

Eye/Face Protection

Faceshield over safety glasses or goggles.

Skin Protection

Avoid skin contact. Chemical-resistant gloves. Lab coat or other work clothing to prevent skin exposure (Long sleeve shirt and long pants). Launder before reuse.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

Wash thoroughly after handling.

9. Physical And Chemical Properties

Appearance

Clear liquid

Odor

Hydrocarbon

Chemical Type: Mixture

Physical State: Liquid

Specific Gravity: 0.76

Solubility: Insoluble in water

Viscosity: Kinematic (40 C): <6.9 cSt

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Incompatible Materials

Oxidizing materials

Conditions To Avoid (Polymerization)

None known

11. Toxicological Information

No Data Available...

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA Information

Waste solutions may meet the RCRA Ignitable characteristic.

MATERIAL SAFETY DATA SHEET

Sika Remover 208

14. Transport Information

Proper Shipping Name

Hydrocarbons, liquid, n.o.s. (Isononane / N-Nonane)

Hazard Class

3

DOT Identification Number

UN3295

DOT Shipping Label

Flammable

Freight Class

PG III

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Fire Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

16. Other Information

HMIS Rating

Health: 2

Fire: 3

Reactivity: 0

PPE: H

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supersedes A Previous MSDS Dated: 06/13/2007

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY

MATERIAL SAFETY DATA SHEET

Sika Remover 208

Disclaimer - Continued

OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

Sika Corporation

Printed Using MSDS Generator™ 2000